



Motor Oil & Lubricants

REXOIL DIAMOND

10W/40 SN/CF

REXOIL DIAMOND 10W/40 is engine oil which perfectly adapted to all types of modern vehicles, passenger cars, SUVs and off-road cars equipped with catalysts and using unleaded fuel or liquefied petroleum gas (LPG). It is particularly suited to turbocharged, multi-value and direct injection engines. Provides superior performance under extreme cold start up conditions. It's not recommended for Diesel particulate filters (DPF) and gasoline catalytic converters (CAT's) vehicles.

Properties

- Provides fuel economy and long service life by excellent viscosity control property.
- It forms extra protection layer against to abrasion by bonding to surface of engines with smart molecules that contains.
- It makes easy to work at cold weather by its viscosity.
- Provides high resistance to tear due to high viscosity index.

Approvals and Specifications

- API SN/SM/SL/CF
- ACEA A3/B3/B4
- Peugeot/Citroën Automobiles B71 2296
- Renault RN0700
- Volkswagen VW50200
- Opel GM-LL-A-025
- BMW Longlife-01
- API CF
- MB-Approval 229.3
- AVTOVAZ (LADA cars)
- Renault RN0710
- Volkswagen VW50500
- Opel GM-LL-B-025
- Porsche A40



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Appearance	Visual	Clear-Bright
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 135
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -27
Total Base Number, mg KOH/g	ASTM D 2896	Min. 7,0