



Motor Oil & Lubricants

REXOIL DIAMOND

5W/30 SM/CF

REXOIL DIAMOND 5W/30 is synthetic engine oil which perfectly adapted to all types of modern vehicles, passenger cars, SUVs and off-road cars equipped and using unleaded fuel or liquefied petroleum gas (LPG). It is particularly suited to turbocharged, multi-valve and direct injection engines. It's not recommended for Diesel particulate filters (DPF) and gasoline catalytic converters (CAT's) vehicles.

Properties

- Shows excellent thermal and oxidation stability
- Contains intelligent molecules that cling to your engine and form an extra layer that protects from start up.
- Provides high resistance to tear due to high viscosity index.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.
- Provides superior performance under extreme cold start up conditions.

Approvals and Specifications

- API SM / API SL
- ACEA A3/B3/B4
- Peugeot/Citroën Automobiles B71 2296
- MB-Approval 229.3
- Volkswagen VW50200
- Renault RN0700
- Opel GM-LL-A-025
- BMW Longlife-01
- API CF
- Porsche A40
- AVTOVAZ (LADA cars)
- MB-Approval 229.5
- Volkswagen VW50500
- Renault RN0710
- Opel GM-LL-B-025



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Appearance	Visual	Clear-Bright
Kinematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5
Viscosity Index	ASTM D2270	Min. 150
Flash Point, °C	ASTM D92	Min. 200
Pour Point, °C	ASTM D97	Max. -33
Total Base Number, mg KOH/g	ASTM D 2896	Min. 7,0